



LONG LIFE COOLANT ANTI-FREEZE RADIATOR COOLANT CONCENTRATE



TECHNICAL DATA SHEET

Product Description

Veedol Longlife Coolant is premium quality radiator coolant concentrate.

Veedol Longlife Coolant is blended using Mono Ethylene Glycol, corrosion inhibitors and other performance enhancers.

At higher concentration Veedol Longlife Coolant offers higher boiling point for achieving optimum engine temperatures and lower freezing point for sub zero ambient temperature applications. It protects against freezing, overheating and cavitation thereby extending the service life.

Veedol Long Life Coolant contains multi-metal corrosion inhibitors which imparts excellent protection against rust and corrosion.

Veedol Longlife Coolant is fully miscible with water

To prepare radiator coolant mix one part of Veedol Longlife Coolant with one part of distilled or demineralized water (50% for severe duty) OR one part of Veedol Longlife Coolant with two parts of distilled or demineralized water (33% for moderate duty).

Following procedure for charging Veedol Longlife Coolant is recommended.

1. Drain existing radiator coolant completely through drain plug
2. Flush system with distilled or demineralized water
3. Fill radiator partly with distilled or demineralized water.
4. Pour appropriate quantity of Veedol Longlife Coolant concentrate into radiator, if required make up with using distilled or demineralized water to achieve full level.
5. Change radiator coolant once in 12 months as corrosion inhibitors continuously get used up during service.

Veedol Longlife Coolant is recommended for round the year use in cooling systems of cars, trucks, LCVs and earthmovers

Typical Properties:

Test Parameters	Typical Values
Colour	Green
Boiling Point, °C	171
pH	8 to 9
Freezing Point, °C (50 vol% in water)	-36

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

VEEDOL INTERNATIONAL DMCC

Unit No. 601 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers
P.O. Box No. 117019 | Dubai | United Arab Emirates
Tel: +971-4-3688416 | Fax: +971-4 3688418 | E-mail : enquiry@veedol.ae
www.veedol.ae

THE PROFESSIONAL'S CHOICE