



AVALON 100 ISO VG 100 PREMIUM HEAVY DUTY ANTI-WEAR HYDRAULIC OIL



HO

TECHNICAL DATA SHEET

Product Description

Veedol AVALON 100 is a premium heavy duty anti-wear hydraulic oil with ISO VG 100 viscosity. Blended from premium quality virgin base oils and fortified with anti-wear, anti-oxidant, anti-rust and anti-foam additives. Veedol AVALON 100 retains high lubricity at elevated temperature even under heavy duty conditions and provides excellent filterability characteristics.

Veedol AVALON 100 is recommended for heavy duty hydraulic systems.

Typical Properties:

Test Parameters	ASTM Method	Typical Values
Density @15 °C, Kg/l	D 4052	0.892
Kinematic Viscosity @ 40 °C, cSt	D 445	100
Viscosity Index	D 2270	95
Flash Point, °C	D 92	240
Pour Point, °C	D 97	-30

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

VEEDOL INTERNATIONAL DMCC

Unit No. 601 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers
P.O. Box No. 117019 | Dubai | United Arab Emirates
Tel: +971-4-3688416 | Fax: +971-4 3688418 E-mail : enquiry@veedol.ae
www.veedol.ae

THE PROFESSIONAL'S CHOICE