



DIESEL STAR PLUS

API CH-4 SAE 15W-40

HIGH PERFORMANCE DIESEL ENGINE OIL

TECHNICAL DATA SHEET

Product Description

Veedol Diesel Star Plus 15W-40 is a high performance, premium diesel engine oil, suitable for modern generation turbocharged / supercharged automobile, heavy duty industrial and off-highway diesel engines.

Performance Specifications:

Veedol Diesel Star Plus 15W-40 meets or exceeds the requirements of:

- API CH-4/SL
- ACEA E7
- ACEA A3/B4
- MB 228.3
- Cummins 20076/20077
- Volvo VDS2
- Mack EOM+
- MTU II
- Caterpillar ECF-1a
- Renault RD-2
- Deutz DQC-II-05
- MAN 3275

Features/Benefits:

- Processed from premium quality virgin base oils and performance additives
- Excellent soot control
- Excellent oxidation and thermal stability
- Outstanding anti-wear properties for protecting heavily loaded engine parts
- Reduced oil consumption
- Maintains engine cleanliness
- Very good low temperature viscometrics for reduced wear at start up

Typical Properties:

Test Parameters	ASTM Method	Typical Values
Density @15 °C, Kg/l	D 4052	0.8795
Kinematic Viscosity @ 100 °C, cSt	D 445	14.96
Viscosity Index	D 2270	138
Flash Point, °C	D 92	222
Pour Point, °C	D 97	-33
TBN,mg KOH/g	D 2896	11.15

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

VEEDOL INTERNATIONAL DMCC

Unit No. 601 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers
P.O. Box No. 117019 | Dubai | United Arab Emirates
Tel: +971-4-3688416 | Fax: +971-4 3688418 | E-mail : enquiry@veedol.ae
www.veedol.ae

THE PROFESSIONAL'S CHOICE