



ELITE™
API – SL/CF 20W-50
MULTIGRADE PREMIUM
ENGINE OIL FOR CARS



PCMO

TECHNICAL DATA SHEET

Product Description

Veedol Elite 20W-50 is a premium quality engine oil with very high thermal and oxidation stability. It exceeds requirements of API SL and is recommended for new generation cars having turbocharged/naturally aspirated fuel-injection gasoline and diesel engines.

The unique detergent-dispersant additives system keeps all contaminants in micro suspension to achieve high engine cleanliness and optimum fuel efficiency. Processed from premium quality virgin base oil, it provides outstanding protection to engine components against wear and corrosion.

Performance Standards:

Meeting the standards of American, Japanese and European cars.

Typical Properties:

Test Parameters	ASTM Method	Typical Values
Density @15 °C, Kg/l	D 4052	0.890
Kinematic Viscosity @ 100 °C, cSt	D 445	19.0
Viscosity Index	D 2270	128
Flash Point, °C	D 92	230
Pour Point, °C	D 97	-24
TBN,mg KOH/g	D 2896	8.0

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

VEEDOL INTERNATIONAL DMCC

Unit No. 601 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers
P.O. Box No. 117019 | Dubai | United Arab Emirates
Tel: +971-4-3688416 | Fax: +971-4 3688418 E-mail : enquiry@veedol.ae
www.veedol.ae

THE PROFESSIONAL'S CHOICE