



HDC 50 API CF SAE 50 HEAVY DUTY DIESEL ENGINE OIL



TECHNICAL DATA SHEET

Product Description

Veedol HDC 50 is suitable for use in turbocharged, supercharged and naturally aspirated diesel engines. It exceeds requirements of API CF and is engines recommended for heavy/light commercial vehicles and cars.

High viscosity oil provides adequate fluid film even under heavy loads at high operating temperatures. Fortified with a unique detergent-dispersant additive system, Veedol HDC 50 removes and keeps all contaminants like soot/sludge in highly dispersed state to protect engine from abrasive and corrosive wear over longer drain intervals. Processed from premium quality virgin base oils and performance additives, provides optimum cooling to all engine components.

Typical Properties:

Test Parameters	ASTM Method	Typical Values
Density @15 °C, Kg/l	D 4052	0.901
Kinematic Viscosity @ 100 °C, cSt	D 445	19.0
Viscosity Index	D 2270	100
Flash Point, °C	D 92	260
Pour Point, °C	D 97	-12
TBN,mg KOH/g	D 2896	11

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

VEEDOL INTERNATIONAL DMCC

Unit No. 601 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers
P.O. Box No. 117019 | Dubai | United Arab Emirates
Tel: +971-4-3688416 | Fax: +971-4 3688418 E-mail : enquiry@veedol.ae
www.veedol.ae

THE PROFESSIONAL'S CHOICE