



MULTIGEAR EXPRESS API GL-4 SAE 140 EXTREME PRESSURE GEAR & TRANSMISSION OIL



TECHNICAL DATA SHEET

Product Description

Veedol Multigear ExPress 140 is a premium automotive gear oil with Extreme Pressure additives. Processed from premium virgin base oils having high viscosity, it offers excellent thermal and oxidation stability. It provides excellent protection to gears and other components even under heavy loads and high operating temperatures.

Veedol Multigear ExPress 140 exceeds requirements of API GL-4 and is recommended for heavily loaded rear axles of Trucks, Buses, LCVs, MUVs and Cars

Typical Properties:

Test Parameters	ASTM Method	Typical Values
Density @15 °C, Kg/l	D 4052	0.910
Kinematic Viscosity @ 100 °C, cSt	D 445	30
Viscosity Index	D 2270	95
Flash Point, °C	D 92	260
Pour Point, °C	D 97	-9

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

VEEDOL INTERNATIONAL DMCC

Unit No. 601 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers
P.O. Box No. 117019 | Dubai | United Arab Emirates
Tel: +971-4-3688416 | Fax: +971-4 3688418 E-mail : enquiry@veedol.ae
www.veedol.ae

THE PROFESSIONAL'S CHOICE