



MULTIGEAR EXPRESS API GL-5 SAE 80W-90 EXTREME PRESSURE GEAR & TRANSMISSION OIL



TECHNICAL DATA SHEET

Product Description

Veedol Multigear ExPress 80W-90 is premium multi-grade automotive gear oil with Extreme Pressure additives. Processed from premium virgin base oils, it offers excellent thermal and oxidation stability. It provides excellent protection to gears and other components even under heavy duty conditions.

Veedol Multigear ExPress 80W-90 exceeds requirements of API GL-5 and is recommended for heavily loaded gear boxes of Trucks, Buses, LCVs, MUVs and Cars.

High viscosity index oil maintains high fluidity at low temperatures and retains higher viscosity at high temperatures. Veedol Multigear ExPress 80W-90 also aids fuel economy.

Typical Properties:

Test Parameters	ASTM Method	Typical Values
Density @15 °C, Kg/l	D 4052	0.898
Kinematic Viscosity @ 100 °C, cSt	D 445	15
Viscosity Index	D 2270	98
Flash Point, °C	D 92	210
Pour Point, °C	D 97	-27

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

VEEDOL INTERNATIONAL DMCC

Unit No. 601 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers
P.O. Box No. 117019 | Dubai | United Arab Emirates
Tel: +971-4-3688416 | Fax: +971-4 3688418 E-mail : enquiry@veedol.ae
www.veedol.ae

THE PROFESSIONAL'S CHOICE