

## TECHNICAL DATA SHEET

### Product Description

Veedol Syntron 5W-40 is a fully synthetic engine oil produced from high quality synthetic base oils and high level performance additives, especially formulated for use in VW, Audi, Skoda and Ford vehicles fitted with VW unit injector diesel engines.

### Performance Specifications:

Veedol Syntron 5W-40 meets the performance requirements of the following:

- VW: 505.01
- ACEA: A3/B3-04, B4-04, C3-10
- API: SN/CF
- BMW: LL-04
- MB: 229.31 229.51
- Porsche
- Renault RN 0700, RN 0710

### Features/Benefits:

- Suitable for use in petrol and diesel engines requiring VW specified 505.01 lubricant performance
- Blended to ensure fuel efficiency, reduced wear and low emissions.
- Mid-low SAPS technology delivers a high level of engine cleanliness and protection from combustion contamination.
- Provides optimum performance and engine protection at temperature extremes and under high performance conditions.

### Typical Properties:

Test Parameters	ASTM Method	Typical Values
Density @ 15°C, Kg/L	D 4052	0.85
Kinematic Viscosity, @ 40°C, cSt	D 445	88
Kinematic Viscosity, @ 100°C, cSt	D 445	14.2
Viscosity Index	D 2270	167
Flash Point (COC), °C	D 92	220
Total Base Number, mg KOH/gm	D 2896	8.6
Pour Point, °C	D 97	-39
CSS Viscosity @ (-) 30 °C, cP	D 5293	4563

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

#### VEEDOL INTERNATIONAL DMCC

Unit No. 601 | Indigo Icon | Plot No. F3 | Jumeirah Lakes Towers  
P.O. Box No. 117019 | Dubai | United Arab Emirates  
Tel: +971-4-3688416 | Fax: +971-4 3688418 | E-mail : enquiry@veedol.ae  
www.veedol.ae

**THE PROFESSIONAL'S CHOICE**